





Standards EN 60903:2003 / IEC 60903:2014 IEC 61482-2 ASTM

Network Type: MV

CGM-0-..-410

Insulating gloves with mechanical protection and Arc FLASHVAC, length: 410 mm

## **Application:**

- · Wellfit finish: soft, supple, durable and ergonomic with high flexibility to ease the work.
- · Convenient to any hand shape.
- · Resistant: latex with reinforced mechanical protection against tearing. To be used without over-gloves.
- · Protection against the thermal hazards of an electric arc 12 cal/cm2. IEC 61482-1-2 APC 2 (box test 7 kA).

## **Features:**

- Electrical insulating gloves, class 0 (1 000 V AC, 1 500 V DC).
- Cut edges.
- Material: bicolor natural latex. (exterior: orange, interior: natural).
- Traceability through flashcode on color-coded label. The color is according to the class.
- · Category: RC (Acid, Ozone, Cold, Oil resistance).





	Reference	Size	Length (mm)	Voltage			Arc	
				Operating Voltage AC	Operating Voltage DC	ATPV (cal/cm²)	Box Test	Category
	CGM-0-10-410	10	410	1 000 V	1 500 V	12	7kA / 30 cm	RC



UID: | TID:::06/14/2025 | SID:::06/14/2025 | Issued:06/14/2025 02:07:48 pm

www.catuelec.com

Last Modification: 04/20/2025 CATU S.A.S. - 10, Avenue Jean-Jaurès - B.P.2 - 92222 Bagneux Cedex Phone: +33 1 42 31 46 00 - Fax: +33 1 42 31 46 32 SICAME GROUP