

CZ-53..

Electrical-rescue carrying kit for an electrical shock rescue

Application :

- Allows an intervention on victims in case of electrical shock.
- Immediately makes available to rescuers all the necessary rescue equipment.

Features :

- Mobile and compact carrying case.

Composition :

- 1 insulated cable cutter 25 kV [CZ-60](#).
- 1 telescopic stick extended lenght 1.5 m [MT-830-P](#).
- 1 hook fitted with a voltage detector (127 V - 90 kV) [CC-127-CS-C](#).
- 1 adhesive demarcation tape L 100 m [AT-5005](#).
- 1 pair of insulating gloves [CG-3-10-NR](#) (for CZ-53), [CG-4-10-NR](#) (for CZ-53-2) with protective bag [CG-36/2](#).
- 1 pair of insulating boots [MV-137/45](#).
- 1 insulating stool.
- 1 "First aid for electric shock victims" poster in french [M-991566](#).



Reference	Description	Voltage
		Operating Voltage AC
CZ-53-2	1 ruban adhésif de délimitation jaune/noir, longueur 100 m 1 paire de gant isolant rouge - IEC 60903 classe 4 – 36 kV 1 étui en tissu pour la protection des gants isolants 1 coupe-câbles isolé – 36 kV. Pour câbles de diamètre maxi 26 mm (sections d'environ 150² cuivre et 150² aluminium). 1 paire de bottes isolantes taille 45, adaptée à la tension de pas <20 kV 1 perche télescopique isolante, longueur déployée 1.5m, tension d'utilisation maximale 45 kV 1 crochet de sauvetage équipé d'un détecteur de tension (127 V à 90 kV) 1 valise électro-secours avec tabouret isolant intégré 1 flacon de talc 1 affiche soins aux électrisés type AM-20-B 1 notice de mise en œuvre	36 000 V